

MIO MVS-4HDMI



Mini HDMI input Multi-viewer

The MIO MVS-4HDMI is a low cost miniature multi-viewer for video/audio monitoring used by OBVan or studio. It supports 4ch. HDMI auto adaptive input. 1 DVI/HDMI output. It is a true multi-view with rich features, such as real time audio/video monitoring and text or picture alarm, built-in router, display layout configuring and display template recall/restore, clock and user defined Logo display, AFD, static UMD & tally, audio UV meter. Built in WEB server. The MIO MVS-4HD is a compact and maintenance free unit. It is a perfect cost-effective display solution for mission critical and live applications in broadcast and pro AV area.

User defined flexible Display Layout with Layout Templates Recall and Restore, Output up to 1920x1080P

Active Format Description for Input Signal

Adjust the transparency and position of UMD and Audio meters freely

Key signal marker with red border

1080i

Video/Audio Monitoring Alarm

4:3/16:9 Safe Marker

HD Server-PGM

Static programable UMD

Keep the original ratio of image to display
Push button to recall display layout

Built in WEB server allows user easily remote control the unit with a WEB browser

Digital/Analog Clock, Countdown timer, Air timer

User Defined Logo

User programable border

Built in router allows user to assign any input to any display window

Wireless Pad can be used as a control console

- Support embedded audio
- Output up to 1080p with selectable embedded audio channel
- User configurable display layout with layout template recall/restore
- Real time Video and Audio monitoring with alarm for video/audio lost, frozen, black video, EDH error
- Flexible output options: 4:3, 16:9, customized aspect ratio with 4:3 or 16:9 safe marker
- Selectable air timer and countdown timers, analog and digital clock. User defined Logo display
- 8 channel audio UV meter, Active Format Description (AFD)
- Built-in router assign any input to any display window & any channel can be enlarged to a full screen
- Static programmable multi-color UMD
- Built-in WEB SERVER allows user to easily remote control the unit with a WEB browser
- Quick key to recall the display templates and change the output resolution
- LED for each input channel signal status and power

Gravue Co., LTD

266 Sargent Rd. Boxborough, MA 01719, USA

Email: sales@gravue.com Web: www.gravue.com

Tel: 001 508 473 3080, Fax: 001 978 263 0789



MIO MVS-4HDMI

Mini HDMI input Multi-viewer



Gra-Vue
WWW.GRAVUE.COM

Easy WEB Setting U I & High Point

Label area

Operation area for channels and other display elements

Choose language Version

Input sources list

Make/Delete signal marker

Layout management

Hot key for windows size and position

Parameters setting area

Speedy layouts save and recall

Drag and drop to change window's signal source

One click to change any configuration

Interface Panel



Gravue Co., LTD

266 Sargent Rd. Boxborough, MA 01719, USA

Email: sales@gravue.com Web: www.gravue.com

Tel: 001 508 473 3080, Fax: 001 978 263 0789



MIO MVS-4HD

Mini HDMI input Multi-viewer



Gra-Vue
WWW.GRAVUE.COM

Technical Specifications

Input	4 x HDMI inputs, Type A
Video Input Format	720p 50/60; 1080i 50/60; 1080p 50/60; Support HDMI signal with 8 channel embedded audio Support HDCP protocol.
Output	DVI-I x 1, female, support HDMI 1.3a protocol
Output Format	HDMI: 1024x768, 1280x720, 1280x800, 1280x1024, 1366x768, 1400x1050, 1600x900, 1680x1050, 1600x1200, 1920x1080
Control	RJ 45 Ethernet for built- in WEB Server, DB15 - RS-232 for serial communication, Tally
Press Button	Display templates recall Load factory default
Power	12 VDC, 1.0A, with lock ring
LED	Power Status Input x 4 signal locking
Temperature	Work: 5-25 °C, storage: 0-40 °C
Physical dimension	152mmx122mmx30mm

Ordering information

MIO MVS-4HD Mini box quad multi-viewer with 4 HD/SD inputs, one DVI/HDMI (up to 1920x1080) with duplicated HDSDI Outputs

MIO MVS-4HDMI Mini box quad multi-viewer with 4 HDMI inputs, one DVI/HDMI (up to 1920x1080)

Gravue Co., LTD

266 Sargent Rd. Boxborough, MA 01719, USA

Email: sales@gravue.com Web :www.gravue.com

Tel: 001 508 473 3080, Fax: 001 978 263 0789

