



Description

Based on Mini BOX platform, MIO-DEC-HD is a small converter which can change analog video to HD/SD-SDI. The analog video can be CVBS/YUV/YC optionally, also 525i30 and 625i25 are supported.


The lights on the Mini box indicate the states of source signal and power, so as to let the user know the information immediately.

Be known for compact function, the converter is widely used in variety of environments, like TV program post production, studio, broadcast, etc.

Interface (Refer to real product)



Block Diagram



Ordering Information

MIO-ENC-HD	HD/SD-SDI to analog video converter
MIO-DEC-HD	Analog video to HD/SD-SDI video converter
MIO-ENC-HD-AUD	HD/SD-SDI to analog video and dual analog audio output converter
MIO-DEC-HD-AUD	Analog video and dual analog audio to HD/SD-SDI video converter

Key Features

- Support analog video to HD/SD-SDI conversion (CVBS/YUV/YC are optional)
- Support 525i30 and 625i25.
- Broadcast quality with 10 bit processing and 48KHz audio sampling
- Indicate lights tell the states of source signal and power immediately
- Based on Mini BOX platform, with high performance, widely used in the fields of studio, broadcast and other places

Specifications

Analog Video Input:

Input interface: 3* BNC connector
(CVBS\YC\YUV optional)
Impedance: 75 ohms

Digital Video Output:

Output interface: 4*HD/SD-SDI, BNC connector
Impedance: 75 ohms
Format: SMPTE 292M; 1.5Gbit/s
SMPTE 259M-C; 270Mb/s
Amplitude: 800mV ±5%
Jitter: <0.2UI

Status Indication:

Power states (Indicate by shining or extinguishing of the red and green LED)

Physics:

Power: 9VDC 1.6A
Size: 123mm*92mm*29mm